



## QUARZOTECH



### 1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Exterior quartz wall paint, based on emulsion copolymers, used in buildings for the protection and decoration of exterior and interior wall surfaces of new and old buildings. Applicable on both mineral substrates and on primers painted with synthetic paints. Thanks to its special formula, QUARZOTECH is highly water-repellent and has excellent alkali resistance, therefore it is used successfully in particularly aggressive environments (areas with sea salt, industrial environments) and also has excellent water proof. , Also featured by an excellent coverage and a good filling power that masks the mild imperfections of the surface.

### 2. COMPOSITION

QUARZOTECH is a paste product based on synthetic resins in aqueous emulsion, quartz flour, light-resistant pigments and atmospheric agents, specific additives. It is free from harmful substances such as solvents and pigments based on lead or chromium.

### 3. METHOD OF APPLICATION

Lime and / or cement mortars are suitable, mortars, mineral or synthetic paintings and finishes, perfectly dry and cohesive. Do not apply on supports where there is evidence of rising or infiltrating humidity  
Apply one coat of DERASOL H20 diluted 1: 1 in water; After a minimum of 12 hours, apply a first coat of QUARZOTECH as a primer diluted with 20% water with a roller .After a minimum of 12 hours apply QUARZOTECH's second coat with a roll dilution of 5% to 15% with water, depending on the degree of filling desired.

### 4. TECHNICAL DATA

**SPECIFIC WEIGHT:** 1570 gr./lt +/- 5%  
**VISCOSITY:** \*\*\*\*\*

**DRYING:** to touch 2 hours at 20°C; **completely:** about 24 ore at 20°C

**APPLICATION TEMPERATURE:** between 5°C and 30°C

**APPLICATION:** Spougue Roller  
Rair Roller, brush or spray.

**COVERAGE** 2,5 – 3 m²/Lt (two coats)

**COLORS:** White

**TINTING:** Coloring can also be achieved by the tinting system: Global Tinting System.

**PACKAGE:** polyethylene cans  
LT14

**DILUTION:** 0-20% with water water depending on the job

**PRESERVATION:** 24 months in the intact packages, away

from temperature changes

**HS-CODE:** 32091000

### 5. ITEM OF SPECIFICATIONS

atmospheric agents, specific additives; After consolidating treatment with a DERASOL hand of Spiver s.r.l. Diluted in 1: 1 ratio in water, with a first coat as a primer of QUARZOTECH of Spiver s.r.l. Diluted with 10% of water with a roller; Apply the second coat of QUARZOTECH with sponge roller or hair roll according to the final effect decided by D.L. Price including material and installation, excluding scaffoldings per square meter. € .....

N.B. The above data may be subject to change. Spiver srl assumes no responsibility for the negative results that depend on applications running outside of its control or due to causes unconnected to the quality of the product.



*Emotion with paint ...*

**SPIVER s.r.l.**

contrada Babbaurra S.S. 122  
93100 Caltanissetta ( CL )

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

[www.spiver.it](http://www.spiver.it) - [info@spiver.it](mailto:info@spiver.it)